



Designation: D1882 – 17 (Reapproved 2021)

Standard Test Method for Effect of Cooling System Chemical Solutions on Organic Finishes for Automotive Vehicles¹

This standard is issued under the fixed designation D1882; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope*

1.1 This test method determines the effect of cooling system chemical solutions on organic finishes used on motor vehicles. Cooling system chemicals include: coolants or corrosion inhibitors, or both, cooling system cleaners or flushes, or both, and stop leak additives.

NOTE 1—This test method is a modification of Method of Test [D1540](#).

1.2 The values stated in SI units are to be regarded as standard. The values given in parentheses after SI units are provided for information only and are not considered standard.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.4 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 *ASTM Standards:*²

[D609](#) Practice for Preparation of Cold-Rolled Steel Panels for Testing Paint, Varnish, Conversion Coatings, and Related Coating Products

[D1176](#) Practice for Sampling and Preparing Aqueous Solutions of Engine Coolants or Antirusts for Testing Purposes

[D1540](#) Method of Test for Effect of Chemical Agents on Organic Finishes Used in the Transportation Industry (Withdrawn 1992)³

3. Summary of Test Method

3.1 Concentrated or diluted cooling system chemical solutions are brought into contact with organic finishes typical of those used on automobiles for 1 h at room temperature. The surface of the finish then is inspected visually for any of the surface changes mentioned in Section 4.

4. Significance and Use

4.1 This test method will distinguish between cooling system chemical solutions that do or do not have a tendency to change the surface appearance when applied to organic finishes used on vehicles. Such changes may be manifested by discoloration, loss of gloss, softening, swelling, or other similar phenomena.

5. Materials

5.1 *Test Panels*—Steel panels, approximately 100 mm by 150 mm (4 in. by 6 in.) shall be prepared in accordance with the Methods of Preparation of Practice [D609](#). The surface of the test panels shall be roughened to 0.25 μm to 0.50 μm (10 $\mu\text{in.}$ to 20 $\mu\text{in.}$) prior to applying the organic finish. These panels shall be coated with an organic finish of the type used on vehicles such as clear coated and non-clear coated thermoset urethane and acrylic urethane finishes. Other finishes and painted panels of varying age and dimensions (24 in.² minimum) may be used upon agreement between the customer and supplier.

6. Test Solution

6.1 The coolant to be tested shall be either a concentrate or a dilution. Sufficient ASTM Type IV water shall be added to yield a solution of 50 % concentration by volume in accordance with Practice [D1176](#), section on Preparation of Solutions Requiring Inclusion of Separated Solids and Liquids. Any separated solids or liquids shall be included in the test material.

¹ This test method is under the jurisdiction of ASTM Committee [D15](#) on Engine Coolants and Related Fluids and is the direct responsibility of Subcommittee [D15.03](#) on Physical Properties.

Current edition approved Sept. 1, 2021. Published September 2021. Originally approved in 1961. Last previous edition approved in 2017 as D1882 – 17. DOI: 10.1520/D1882-17R21.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ The last approved version of this historical standard is referenced on www.astm.org.

*A Summary of Changes section appears at the end of this standard



6.2 Other cooling system chemicals shall be tested both without dilution and at a typical use concentration as indicated by instructions on the label. Any separated solids or liquids shall be included in the test material.

7. Procedure

7.1 Conduct the test at $25^{\circ}\text{C} \pm 5^{\circ}\text{C}$ without humidity control.

7.2 Select a test panel prepared in accordance with Section 5. Place sufficient test solution on the surface of the test panel to form spots approximately 25 mm (1 in.) in diameter.

7.3 After 1 h, wipe the surface with a wet cloth, buff with a soft, dry cloth and examine the finish for visual and physical evidence of the effects listed in Section 4.

7.4 Lightly polish the test surface with any well-known

persons to be unobjectionable.

8. Report

8.1 The report shall include the following:

8.1.1 Product and concentration tested.

8.1.2 Coating systems employed.

8.1.3 Type and appearance of the effect obtained on the test panel, as described in Section 4.

8.1.4 Any change in surface effect brought about by use of a polishing agent and by sunlight.

9. Precision and Bias

9.1 *Precision*—It is not practicable to specify the precision of the procedure in this test method because the results are subjective observations.

9.2 *Bias*—There is no acceptable reference material suitable